

(19)

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 134 443 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
19.09.2001 Bulletin 2001/38

(51) Int Cl.7: **F16C 25/06**

(21) Application number: 01830166.3

(22) Date of filing: 13.03.2001

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Perni, Federico**
Trevi (PG) (IT)
• **Pizzoni, Luciano**
Foligno (PG) (IT)
• **Master, Brett**
EPSOM, New Zealand (NZ)

(30) Priority: 15.03.2000 IT RM200134

(71) Applicant: **Umbra Cuscinetti S.p.A.**
06034 Foligno (IT)

(74) Representative: **Lanzoni, Luciano**
c/o Bugnion S.p.A.
Via Vittorio Emanuele Orlando, 83
00185 Roma (IT)

(54) A device for measuring and adjusting preloading on bearings

(57) A device for measuring and adjusting pre-loading on bearings, measuring and adjusting both the mounting and operating loads, wherein means for applying a preloading and return means are positioned to constitute a single actuator organ (2), comprising two ring elements for distributing the preloading (20, 21), whereof at least one is destined to act against the outer

race of a bearing and containing interposed between them a kinematic chain imparting thereon a thrust determined by the action of two or more piezoelectric or magnetostrictive means (22) for applying the preloading and return means (23); to said actuator organ (2) being associated an annular loading cell (3) connected in an external feedback control system for measuring and adjusting said preloading.




FIG. 1

Description

[0001] The present invention relates to a device for measuring and adjusting preloading on bearings, i.e. for measuring and adjusting mounting and operating loads on bearings, which employs piezoelectric and magnetostrictive means to apply such preloading. As is well known, piezoelectricity is the phenomenon whereby some crystalline bodies, generically called piezoelectric crystals, are electrically polarised as a consequence of a mechanical deformation of elastic nature, or vice versa are elastically deformed if subjected to the action of an electrical field. This second effect, known as inverse piezoelectric effect or Lippmann effect, is the one used in the present invention. Similarly, for the same invention it is possible to make use of the magnetostriction phenomenon, consisting of the fact that the dimensions of a body vary when it is magnetized or when in any case its magnetization is varied. In the remainder of the description, materials subject to the piezoelectric effect are mentioned, but this is not to be taken as limiting.

[0002] The characteristics of these materials have found application, among other fields, also in the means for preloading bearings, where they replaced purely mechanical adjustment devices able to provide a variable stiffness for a bearing assembly. Examples of this kind are represented by machining on electrical mandrels or drill heads where the bearing assembly must have high stiffness and low speed of rotation, typical of roughing operations, and low stiffness for high speeds of rotation, as in finishing operations. As is well known, another factor is represented by thermal expansion which can lead, in the rolling areas, to operating overloads which impact on the working life of the bearings.

[0003] The US patent no. 4,850,719 in the name of Moseley et al., for instance, describes a variable stiffness bearing which uses piezoelectric means to apply a variable preload force to the bearing. The piezoelectric means preferably used are piezoelectric wafers, positioned between two bearings around a shaft and alternatively connected to alternating voltage and to ground to allow the wafers to become distorted in a manner directly proportional to the potentials applied. The wafers are positioned consecutively side by side and, with their deformation due to a variation of the applied potential, they exert a longitudinal force, parallel to the axis of the bearings. Moseley's device has no means for adjusting the preloading, and thus serves solely to adjust the stiffness of the bearing.

[0004] Also known, in any case, is a device for adjusting the preloading for a main shaft bearing from the publication of Japanese Patent no. 8-35220 in the name of Hitachi Seiki Co. Ltd. It comprises means, generally springs, for imparting a thrusting force in a single direction from a side of the outer race of a bearing, means for conferring a preloading, in general to the rolling support through the outer race of the bearing pressing the other side of the outer race in the opposite direction

against the thrusting means. Moreover, a unit is provided for measuring the preloading applied to the outer race by the preloading conferring unit, and control means including means for storing the optimal preloading value for the speed of rotation of the main shaft, means for comparing the optimal preloading, extracted from the data storing means for values corresponding to the speed of rotation of the main shaft, with an effective preloading measured by the preloading measuring means.

[0005] The aforementioned known device describes a device for adjusting the preloading in which the thrusting means and the counteracting or elastic return means are distinct components of the device, positioned in respectively opposite parts of the bearing subjected to stiffening.

[0006] A device of this kind is particularly complex and not always applicable to a bearing on already operating shafts.

[0007] Also known is a device for adjusting the preloading for a bearing, disclosed in Japanese Patent no. 8-25106 in the name of Honda Giken Kogyo. The adjustment of the preloading in this case is obtained by means of pressure in the axial direction by means of a piezoelectric element positioned on the side of the bearing that sustains a rotating shaft. The device for adjusting the preloading comprises a sensor to measure the load acting on the outer race of the bearing and means for commanding a voltage applied to the piezoelectric element as a function of the measured load. The means for applying the preloading are represented by a cylinder whose piston applies a force on a slide applied against the outer race at the opposite side of the piezoelectric element. In the Honda device, it is possible to adjust the preloading on a pair of bearings thanks to respective sensors, but the Honda device comprises, like the Hitachi device, thrusting means that are distinct from the counteracting or elastic return means and positioned on opposite parts relative to the bearings. As in the Hitachi device, also in the Honda device the piezoelectric means for applying the preloading is formed by wafers positioned mutually side by side. They exert a direct action on the bearings, concentrated in some points of the outer race. The means for conferring the preloading are separated from the thrusting means and thus the whole preloading device is substantially divided into at least two parts located on the opposite sides of the bearings. In the Honda device the sensors are displacement sensors positioned in contact with the peripheral surface of the outer race of the bearing; they are able to allow a measurement of the load on the bearing only if it is assumed that the inner races remain fixed in position. Since this cannot be verified with certainty, the indeterminate nature of the measurement leads to an inadequate operation of the entire device.

[0008] The positioning of the sensors, located in proximity to the various bearings, and their number increase the complexity of the device, both in terms of construc-

tion and operation.

[0009] As stated previously, such complexity in known devices makes it impossible to introduce them on existing bearing assemblies without substantial modifications and heavy adaptations of the component parts.

[0010] The present invention therefore aims to overcome the drawbacks of the devices for adjusting the preloading known from the prior art.

[0011] An aim of the present invention is to obtain a device of the type mentioned above, in particular of the type using piezoelectric and magnetostrictive means, which has a mechanically compact structure allowing it to be installed on bearing assemblies replacing or being added to the external spacer, in existing or newly designed machines.

[0012] Another aim of the invention is to obtain a device that is able to measure the axial load on the bearings due to tightening during the assembly phase, to the working axial thrusts, to the centrifugal forces and the thermal expansions of the machine whereon the bearings are mounted.

[0013] Another aim of the invention is to obtain a device that is able to suit the stiffness of the bearing assemblies according to the type of machining operation (drilling, boring, milling, contouring, etc.), to the type of tools employed, to the type of material to be machined or to the precision to be obtained on the finished piece.

[0014] A further aim of the invention is to obtain a device that allows to adjust the load thanks to a feedback control system between the current measurement and the predefined and stored load values according to the dimensions that cause the load itself to vary.

[0015] The invention, as it is characterised by the claims that follow, solves the problem of providing a device for measuring and adjusting preloading on bearings surrounded by a casing, of the type comprising means for applying a preloading, in the form of one or more piezoelectric or magnetostrictive elements, able to apply a thrust defining a preloading on the outer race of bearings, reaction means for applying a force counteractive the preloading force, sensor means for instantaneously measuring the load and feedback control system for adjusting said load, which, from a general point of view, is characterised in that said means for applying a preloading and said reaction means are positioned to constitute a single actuator organ, comprising two ring elements for distributing the preloading, opposite and coaxial to the shaft, a first ring and a second ring, whereof at least one is destined to act against the outer race of a bearing and containing, interposed between them, two or more piezoelectric or magnetostrictive means for applying the preloading and return means associated to connecting elements between said ring elements; to said actuator organ being operatively adjacent an annular loading cell connected with an external feedback control system for measuring and adjusting said preloading.

[0016] Further features and advantages of the invention shall become more readily apparent from the de-

tailed description that follows of an embodiment, illustrated purely by way of non limiting indication in the accompanying drawings, in which:

- Figure 1 shows a perspective view of an actuator organ of the device for measuring and adjusting the preloading on bearings according to the present invention;
- Figure 2 shows a perspective schematic view of a detail of the actuator organ of Figure 1;
- Figure 3 shows a perspective schematic view of another detail of the actuator organ of Figure 1;
- Figure 4 shows a top schematic view of a loading cell of the device for measuring and adjusting the preloading on bearings according to the present invention;
- Figure 5 shows a view of a detail of the loading cell of Figure 4;
- Figure 6 shows a schematic axial section of a first embodiment of the device for measuring and adjusting the preloading on bearings according to the present invention;
- Figure 7 shows a schematic axial section of a second embodiment of the device for measuring and adjusting the preloading on bearings according to the present invention; and
- Figure 8 shows a block diagram of a feedback control system that employs the device according to the present invention.

[0017] With reference to the figures, a preferred but not exclusive embodiment of the device for measuring and adjusting the preloading on bearings according to the present invention is shown. In particular, from Figures 6 through 8, which show the application of the device, globally indicated as 1, on a bearing assembly 10 about a main shaft 11, it is evident that it is constituted by an actuator organ 2 and by a loading cell 3.

[0018] With reference to Figure 1, which is an axonometric view of the actuator device 2, two ring elements 20, 21 for distributing the preloading, destined to be mutually opposite and mounted coaxially to the main shaft 11, contain interposed between them a kinematic chain imparting on them a thrust determined by the action of two or more piezoelectric or magnetostrictive means for applying the preloading, generically indicated as 22, and return means, generically indicated as 23. The return means 23 are substantially thrust means serving essentially to counteract the means 22 for applying the preloading. The return means 23 are associated to connecting elements 24 between the ring elements 20, 21.

[0019] The means 22 for applying the preloading are formed by single elements or by wafers of piezoelectric materials or of a material operating according to a known magnetostrictive effect. In Figure 1 the means 22 for applying the preloading are shown, by way of example, in the form of bars with quadrangular sections, but they may have any different shape suitable for the pur-

pose.

[0020] According to the invention, in the currently preferred embodiment, said actuator organ 2 comprises, interposed between said ring elements 20, 21 two or more preloading units constituted each by two preloading means 22 mutually opposite and acting in a converging manner on a connecting element 24, shown in particular in Figure 3. Each preloading means 22 is supported in an articulated manner, at one of its ends, by the connecting element 24, and at its other end by a strut, generically indicated as 25 and shown in particular by itself, in a possible preferred embodiment, in Figure 2. Advantageously, in an embodiment, each strut 25 is formed by two "C" shaped sections coupled mutually opposite along their core or formed in a single piece of identical shape. Each strut 25 is mounted in bridge-like fashion between the two ring elements 20, 21 so as to be fastened rigidly with screws 125 to the ring element 20 and to be only set against the other ring element 21. Each strut 25, in the illustrated embodiment, is advantageously destined to support in articulated fashion at both its sides two opposite preloading means 22 afferent to two consecutive preloading unit thereby constituting a circumferential kinematic chain of the preloading units in the gap defined by said two ring elements 20, 21.

[0021] Each preloading means 22 is positioned inclined between the two ring elements 20, 21 only relative to their axis, or, as shown in Figure 1, both relative to their axis and relative to their radial direction.

[0022] The preloading means 22 are also articulated at their respective ends to a connection element 24 and to a strut 25 by means of hinges 26. In an embodiment, each of these hinges 26 is obtained by means of a reduction in section of a portion 126 for joining and sustaining the preloading means 22 with the respective connecting elements 24 and with the strut 25. Naturally, said hinges 26, shown by way of example as virtual hinges, functionally co-operating with said return means, can constructively be obtained in the form of actual hinges. Each connecting element 24 is formed, for example, similar to a T section bar, fastened with the free end of its core with screws 124 to the ring element 20 and with the wings, at the end whereof project said joining and sustaining portions 126, with screws 127 to the ring element 21. Therefore, the preloading elements 22 converge towards the ends of the wings of the connecting element 24. In this way, the deformation increasing the longitudinal dimension of a pair of preloading elements 22 of a preloading unit applies a thrust on the two elements 20, 21 away from each other, against the action of the return means 23 in the form of a spring or other elastic return means. The inclined and converging disposition of the preloading elements 22 determines, on the connecting element 24, a resulting force multiplying the preloading thrust, thereby increasing the displacement effect obtainable from a simple axial disposition of the preloading elements 22.

[0023] The return means 23 is positioned transversely

to join the connecting element 24 fastened on the ring element 21 and the ring element 20. The return means 23 comprises elastic means presenting a reduced resistance to traction in the direction in which the two ring elements 20, 21 are moved apart and with sufficient characteristics of elastic return.

[0024] With reference to the Figures 4 and 5, the loading cell 3 is constituted by an annular element bearing on its face oriented towards the outer race of a bearing a multiplicity of identical circumferential joists arranged in succession on an annular body 31. Each of said joists 30 presents, consecutive to the others, one of its ends 32 with reduced section and shaped in overhang in correspondence with a concavity 33 presented by the annular body 31. In correspondence with the upper edge of said overhang end 32 (Figure 5) are provided respective projections 34 destined to bear with pressure against the outer race of a bearing, whilst, by way of example, said annular body 31 finds useful support seat in a circumferential depression 131 presented by the outer surface of the first ring element 20 of the actuator organ 2 (Figure 1). In correspondence with the base of each of said overhang ends 32, in corresponding multiplicity, are provided sensors - strain gages 35 positioned in pairs in bridge fashion on both sides of the overhang ends 32.

[0025] The loading cell 3 is therefore able directly to transmit, through said projections 34, the preloading pressure determined by the adjacent actuator organ 2 on the outer ring of a bearing, measuring its value and any consequent displacements through the flexion of said overhang ends 32 measured by the pair of sensors - strain gauges 35 which, in a manner known in itself, send the respective signals to an external feedback control system for measuring and adjusting the preloading, or the mounting and operating loads on the bearing, shown in the diagram of Figure 8.

[0026] Figures 6 and 7 show two applications of the device according to the invention to a bearing assembly about the main shaft 11. With reference to Figure 6 the actuator organ 2 is interposed between a spacer 40 integral with the casing 41 which surrounds the shaft and the loading cell 3, in contact against the outer race 42 of a bearing. Superiorly, the device 1, comprising the actuator organ 2 and the loading cell 3, are shown with simple dashed line, whilst inferiorly they are distinctly shown schematically to represent the actual shape of the device.

[0027] With reference to Figure 7, the actuator organ 2 is located between the outer race 43 of a first bearing and the outer race 44 of a second bearing, with the interposition of the loading cell 3.

[0028] The device, constituted by the actuator organ 2 and by the loading cell 3, is part of an external feedback control system for measuring and adjusting the preloading shown in the diagram of Figure 8. It further comprises a control unit 4, having upstream a calibration unit 5 and downstream a power supply unit 6 for the ac-

tuator organ 2. The loading cell 3 in turn is connected to the control unit 4. The loading cell 3 is further connected to a unit 7 for recording the load conditions.

[0029] The advantages of the device according to the present invention are summarised below.

[0030] The compactness of the device as an autonomously operating organ allows for its easy installation on existing or newly designed machines. It has positive repercussions on a reduction in fabrication and installation costs.

[0031] The device is able, with its kinematic mechanism for multiplying the preloading thrust, completely to meet the demand for motion to compensate for thermal and centrifugal effects and for deformations in the contact areas and hence to vary the load according to useful values, controlled and selected as a function of the aforesaid effects.

[0032] The location of the loading cell in line, interposed between the outer race of the bearing and the actuator organ, enables to measure the mounting loads due to the tightening of the locking rings of the bearings or other elements, the axial operating loads due to the loads on the tools, the thermal loads due to the difference in expansions of the bodies. Moreover, the position of the cell allows, in an initial calibration, to measure the loads due to centrifugal forces.

[0033] Since the loading cell measures the loads actually applied on the bearings, the acquisition of the entire loading history of the bearings is enabled. By recording these data, it is then possible to perform the programmed maintenance of the bearings, scheduling their replacement, as needed, upon reaching the expected service life.




[0034] Naturally, the invention thus conceived can be subject to numerous technically equivalent modifications and variations, without thereby departing from the scope of the inventive concept which characterises it as claimed below.

Claims

1. A device for measuring and adjusting preloading on bearings surrounded by a casing, of the type comprising means for applying a preloading, in the form of one or more piezoelectric or magnetostrictive elements, able to apply a thrust defining a preloading on the outer race of bearings, reaction means for applying a force counteractive the preloading force, sensor means for instantaneously measuring the load and feedback control system for adjusting said load, **characterised in that** said means for applying a preloading and said reaction means are positioned to constitute a single actuator organ (2), comprising two ring elements for distributing the preloading, opposite and coaxial to the shaft (11), a first ring (20) and a second ring (21), whereof at least one is destined to act against the outer race of a bearing and containing, interposed between them, two or more piezoelectric or magnetostrictive means (22) for applying the preloading and return means (23) associated to connecting elements (24) between said ring elements (20, 21); to said actuator organ (2) being operatively adjacent an annular loading cell (3) connected with an external feedback control system for measuring and adjusting said preloading.
2. A device as claimed in claim 1, **characterised in that** said actuator organ (2) comprises, interposed between said ring elements (20, 21), two or more preloading units constituted each by two preloading means (22), positioned mutually opposite and acting in a converging manner on respective wings of a connecting element (24); each preloading means (22) being supported in an articulated manner, at one of its ends, by said connecting element (24), and, respectively, at its other end by a strut (25) mounted in bridge-like fashion between the two ring elements (20, 21), in order to be fastened with screws (125) to the first ring element (20) and to be set against the second ring element (21).
3. A device as claimed in claim 2, **characterised in that** said strut (25) is destined to support in articulated fashion at both its sides two opposite preloading means (22) afferent to two consecutive preloading unit thereby constituting a circumferential kinematic chain of the preloading units in the gap defined by said two ring elements (20, 21).
4. A device as claimed in claim 1, **characterised in that** each preloading means (22) is positioned inclined between the two ring elements (20, 21) relative to their axis.
5. A device as claimed in claim 1, **characterised in that** each preloading means (22) is positioned inclined between the two ring elements (20, 21) both relative to their axis, and relative to their radial direction.
6. A device as claimed in claim 2, **characterised in that** a hinge (26) is provided in a junction portion (126) between each connecting element (24) and each preloading means (22) and between each strut (25) and each preloading means (22).
7. A device as claimed in claim 6, **characterised in that** said hinge (26) is obtained through a weakening of said junction portion (126).
8. A device as claimed in claim 1, **characterised in that** said return means (23) are positioned transversely to join said connecting element (24) fastened with screws (127) on the ring element (21).

and the ring element (20) fastened with screws (124), said return means (23) comprising elastic means presenting a reduced resistance to traction in the direction in which the two ring elements (20, 21) are moved apart and with sufficient characteristics of elastic return. 5

9. A device as claimed in claim 1, **characterised in that** said loading cell (3) is constituted by a multiplicity of identical circumferential joists (30), arranged in succession on an annular body (31), each of which joists (30) presents, consecutively to the others, one of its ends (32) with reduced section and shaped in overhang in correspondence with a concavity (33) presented by the annular body (31); in correspondence with the upper edge of said overhang ends (32) being provided respective projections (34) and in correspondence with the base of each of said overhang ends (32), in corresponding multiplicity, being provided sensors - strain gages (35) positioned in pairs in bridge fashion on both sides of the overhang ends (32) and connected with an external feedback control system for measuring and adjusting the preloading. 10
15
20
25
10. A device as claimed in claim 9, **characterised in that** said projections (34) are destined to bear with pressure against the outer race of a bearing. 25
11. A device as claimed in claim 1, **characterised in that** said actuator organ (2) is positioned between a spacer (40) integral with the casing (41) that surrounds the shaft (11) and the outer race (42) of a bearing, with the interposition of the loading cell (3). 30
35
12. A device as claimed in claim 1, **characterised in that** said actuator organ (2) is positioned between the outer race (43) of a first bearing and the outer ring (44) of the second bearing, with the interposition of the loading cell (3). 40
13. A device as claimed in claim 1, **characterised in that** said external feedback control system for measuring and adjusting the preloading, whereof said actuator organ (2) and said loading cell (3) are parts, comprises a control unit (4), having upstream a calibration unit (5) and downstream a power supply unit (6) for the actuator organ (2); the loading cell (3) in turn being connected to said control unit (4). 45
50
14. A device as claimed in claim 13, **characterised in that** the loading cell (3) is further connected to a unit (7) for recording the load conditions. 55






FIG. 5




FIG. 4







FIG. 8



THIS PAGE BLANK (USPTO)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 134 443 A3**

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
02.01.2003 Bulletin 2003/01

(51) Int Cl.7: **F16C 25/06**, **F16C 19/08**,
F16C 35/063, **F16C 35/077**,
B23Q 1/26

(43) Date of publication A2:
19.09.2001 Bulletin 2001/38

(21) Application number: **01830166.3**

(22) Date of filing: **13.03.2001**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Perni, Federico**
Trevi (PG) (IT)
• **Pizzoni, Luciano**
Foligno (PG) (IT)
• **Master, Brett**
EPSOM, New Zealand (NZ)

(30) Priority: **15.03.2000 IT RM200134**

(71) Applicant: **Umbra Cuscinetti S.p.A.**
06034 Foligno (IT)

(74) Representative: **Lanzoni, Luciano**
c/o Bugnion S.p.A.
Via Vittorio Emanuele Orlando, 83
00185 Roma (IT)

(54) **A device for measuring and adjusting preloading on bearings**

(57) A device for measuring and adjusting pre-loading on bearings, measuring and adjusting both the mounting and operating loads, wherein means for applying a preloading and return means are positioned to constitute a single actuator organ (2), comprising two ring elements for distributing the preloading (20, 21), whereof at least one is destined to act against the outer

race of a bearing and containing interposed between them a kinematic chain imparting thereon a thrust determined by the action of two or more piezoelectric or magnetostrictive means (22) for applying the preloading and return means (23); to said actuator organ (2) being associated an annular loading cell (3) connected in an external feedback control system for measuring and adjusting said preloading.




FIG. 1



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 83 0166

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 377 145 A (INST PRODTech KARLSRUHE) 11 July 1990 (1990-07-11)	1	F16C25/06
A	* the whole document *	9,12-14	F16C19/08
A	EP 0 750 124 A (TORRINGTON CO) 27 December 1996 (1996-12-27)	1	F16C35/063
A	* the whole document *		F16C35/077
A	JP 03 009116 A (BROTHER IND LTD) 17 January 1991 (1991-01-17)	1,9-11, 13,14	B23Q1/26
A	* abstract; figure 1 *		
A	JP 08 035520 A (HITACHI SEIKI CO LTD) 6 February 1996 (1996-02-06)	1,9,10, 13,14	
A	* abstract; figure 1 *		
A	JP 01 266320 A (NIPPON SEIKO KK) 24 October 1989 (1989-10-24)	1,9,12, 13	
A	* abstract; figures *		
A	EP 0 534 537 A (S K F IND TRADING & DEV COMPAN) 31 March 1993 (1993-03-31)	1	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
	* abstract *		F16C
	* column 1, line 43 - column 2, line 54; figures *		B23Q

The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 15 October 2002	Examiner Prieto Sanz, M.D.
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons a : member of the same patent family, corresponding document	

EPO FORM 1503 03 82 (P04CC1)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 83 0166

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

15-10-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0377145	A	11-07-1990	DE 3900121 A1	19-07-1990
			EP 0377145 A2	11-07-1990
			JP 2276938 A	13-11-1990
EP 0750124	A	27-12-1996	CA 2179477 A1	22-12-1996
			DE 69605154 D1	23-12-1999
			DE 69605154 T2	17-08-2000
			EP 0750124 A2	27-12-1996
JP 03009116	A	17-01-1991	NONE	
JP 08035520	A	06-02-1996	NONE	
JP 01266320	A	24-10-1989	NONE	
EP 0534537	A	31-03-1993	NL 9101579 A	16-04-1993
			EP 0534537 A1	31-03-1993

THIS PAGE BLANK (USPTO)